

Maxol Lawnmower Oil

Description:

An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam -
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

Performance Level:

API SF/CG-4/GL-4
ACEA E3, MIL-L-2104D
Allison C4
Cat TO-2
Ford M2C159-C / M2C134-D
John Deere J27 / J20C
Massey Ferguson CMS M1145 / M1144 / M1139
Massey Ferguson CMS M1143 / M1135
MB 227.1
NH 410B
ZF TE-ML 06B / 07B

Application:

This multifunctional lubricant () has been developed to achieve one single lubricating oil that is able to lubricate:*

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems (*) a so-called Super Tractor Oil Universal = STOU

Typical Characteristics:

Density at 15°C, kg/l	0,870
Viscosity -25 °C, mPa.s	4730
Viscosity 40 °C, mm²/s	70,60
Viscosity 100 °C, mm²/s	11,40
Viscosity Index	154
Flash Point COC, °C	228
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

