

## Maxol Bio Hydrasynth Eco 46

### Description:

This is a high-quality hydraulic oil based on biodegradable synthetic esters under addition of additives to obtain the following properties:

- a high and stable viscosity index
- excellent wear
- preventing properties
- a very good activity against corrosion
- an excellent stability against oxidation (even at high temperatures)
- very good deaerating and foam suppressing properties
- a good compatibility with seals and gaskets made from synthetic material
- a very low pour point
- good water separation
- reduced harm for water and soil during use
- contains a large fraction of biobased material

### Performance Level:

EU Ecolabel
ISO 15380 HEES
Swedish Standard SS 15 54 34
Biodegradability according OECD 301 B > 70%
Elastomer compatibility:
Tested Nitrile Butadiene NBR1-pass
Tested Fluor Carbon FMK2-pass

### Application:

This biodegradable hydraulic oil is of high quality and suitable for heavy duty hydraulic systems of earthmoving equipment and permanent installations, that have to work under high pressures over a wide temperature range. This hydraulic oil is especially developed for situations where pollution of the environment is expected and and where very high operating temperatures can be realised.

### Typical Characteristics:

Density at 15 °C, kg/l	0,919
Viscosity 40 °C, mm <sup>2</sup> /s	47,00
Viscosity 100 °C, mm <sup>2</sup> /s	9,35
Viscosity Index	192
Flash Point COC, °C	292
Pour Point, °C	-33
Acid Number mgKOH/g	1,31

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

