Maxol Lubricants

Technical Data

Maxol Indusol 460

Description:

High-grade industrial gear oil, based on mineral oil, under addition of lead-free Additives to obtain the following properties:
- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good rust
- and corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

Performance Level:

AGMA 9005-F16 (AS)
AIST (US Steel) 224
David Brown S1.53.101 E
DIN 51517-3 CLP
ISO 12925-1 Type CKD

Application:

To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

Typical Characteristics:

Density at 15 °C, kg/l	0,900
Viscosity 40 °C, mm²/s	460,00
Viscosity 100 °C, mm²/s	30,50
Viscosity Index	95
Flash Point COC, °C	255
Pour Point, °C	-12

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST