

## Maxol Superfleet CI-4 15W/30

### Description:

Maxol Superfleet CI-4 is a modern, universal applicable engine oil produced with high-quality, solvent-refined base oils and a well-balanced choice of additives.

- Very good detergency prevents deposits in the engine
- Very good dispersion that prevents from precipitation and sludge
- Powerful action against corrosion and foam
- High and stable viscosity index
- Low sulphated ash content
- Powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

### Application:

This universal engine oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo-loading, under heavy operating conditions and all the year round. This oil is excellent suitable for mixed fleets and can be applied in e.g. Euro 3 and Euro 4 engines. Due to its special composition longer drain intervals are possible with this motor oil.

### Performance Level:

ACEA A3/B4, E7
API CI-4/SL
MB 228.3
MAN M 3275
Cummins CES 20078
Deutz DQC III-10

### Typical Characteristics:

Density at 15 °C, kg/l	0.883
Viscosity -20 °C, mPa.s	5840
Viscosity 40 °C, mm <sup>2</sup> /s	83.69
Viscosity 100 °C, mm <sup>2</sup> /s	11.70
Viscosity Index	132
Flash Point COC, °C	212
Pour Point, °C	-39
Total Base Number, mgKOH/g	10.7

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

