

Maxol 4T Motorcycle Oil 10W/40

Description:

Maxol 4T Motorcycle Oil 10W/40 is a new generation semi-synthetic engine oil for four-stroke motorcycles, formulated with high-quality mineral and synthetic base oils combined with specially developed balanced additives.

- High and stable viscosity index
- Good cold start properties
- Optimal friction characteristics
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion

Application:

This oil is specially developed for the lubrication of four-stroke motorcycles so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs.

Performance Level:

API SL
JASO MA2
JASO MA

Typical Characteristics:

Density at 15 °C, kg/l	0.871
Viscosity -25 °C, mPa.s	5560
Viscosity 40 °C, mm ² /s	101.00
Viscosity 100 °C, mm ² /s	15.00
Viscosity Index	156
Flash Point COC, °C	210
Pour Point, °C	-30
Total Base Number, mgKOH/g	7.7
Sulphate Ash, %	0.94

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

