

## Maxol Semi-Synthetic 5W/30

### Description:

Maxol Semi-Synthetic 5W/30 is a fuel economy motor oil produced with special selected mineral and synthetic base oils and a well-balanced choice of advanced additives.

- Lower fuel consumption
- High and stable viscosity index
- High resistance against shearing
- Fast cold start
- Very strong resistance against oxidation
- Safe lubrication film at high temperatures
- Very good detergency and dispersion power
- Very strong protection against wear, corrosion and foaming

### Application:

This fuel economy motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications stated below. This motor oil is specially developed for those cars that ask for motor oils that fulfil the requirements of the Ford M2C913-A and Ford M2C913-B.

### Performance Level:

ACEA A5/B5
API SL/CF
Ford M2C913-A/B

### Typical Characteristics:

Density at 15 °C, kg/l	0.854
Viscosity -30 °C, mm <sup>2</sup> /s	5850
Viscosity 40 °C, mm <sup>2</sup> /s	58.60
Viscosity 100 °C, mm <sup>2</sup> /s	10.10
Viscosity Index	161
Flash Point COC, °C	230
Pour Point, °C	-33
Total Base Number, mgKOH/g	8.1

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

