

Maxol Supersynth 5W/30

Description:

A universal, synthetic fuel economy motor oil developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

This universal, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level:

ACEA C2, C3
API SP
MB-Approval 229.52 / 229.51 / 229.31
BMW Longlife-04
GM dexos 2
Opel OV 040 1547 - D30 / G30
VW 505.00 / 505.01

Typical Characteristics:

Density at 15°C, kg/l	0,851
Viscosity -30 °C, mPa.s	5450
Viscosity 40 °C, mm²/s	69,60
Viscosity 100 °C, mm²/s	12,30
Viscosity Index	179
Flash Point COC, °C	228
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,75

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

