

## Maxol Tractor Trans Plus

### Description:

A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefore applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

### Application:

This very high-quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

### Performance Level:

API GL-4
Allison C4
Cat TO-2
Case MS 1210
CNH MAT 3540 / 3525
FNHA-2-C-200.00 / 201.00
Ford M2C86-C / M2C134-D
John Deere J20C/D
Massey Ferguson M1141 / M1143 / M1145
Valtra G2-08
Volvo WB 101 (97303)
ZF TE-ML 03E / 05F / 06K / 17E / 21F

### Typical Characteristics:

Density at 15°C, kg/l	0,881
Viscosity 40 °C, mm <sup>2</sup> /s	60,00
Viscosity 100 °C, mm <sup>2</sup> /s	9,30
Viscosity Index	136
Flash Point COC, °C	215
Pour Point, °C	-45
Total Base Number mgKOH/g	6,4
Sulphate	1,49

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

