

Maxol Multivis 68

Description:

Maxol Multivis 68 is a high-grade EP multigrade hydraulic oil based on carefully selected solvent-refined base oils under addition of additives.

- High and stable viscosity index
- Excellent wear-preventing properties
- Very good activity against corrosion
- Excellent stability against oxidation
- Very good demulsification properties
- Very good deaerating and foam suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

Application:

This hydraulic fluid is of tailor-made quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that have to work under high pressures over a wide temperature range. This fluid is **not** compatible in systems containing parts or equipment with a silver lining.

Performance Level:

AFNOR NF E 48-603 HV
ASTM D 6158 HV
Bosch Rexroth RDE 90220
Cincinnati Machine P-69
Denison HF-0/HF-1/HF-2
DIN 51524-3 HVLP
Eaton 03-401-2010 Rev-1 (35VQ25A) / Brochure 694
Eaton (Vickers) M-2950-S / I-286-S3
GB 11118.1
GM LS-2
ISO 11158 HV / 6743-4 HV

Typical Characteristics:

Density at 15 °C, kg/l	0.866
Viscosity 40 °C, mm ² /s	68.00
Viscosity 100 °C, mm ² /s	11.20
Viscosity Index	150
Flash Point COC, °C	210
Pour Point, °C	-36
Acid number, mgKOH/g	0.40
Sulphate Ash, %	0.06

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

