

Maxol Powertrac 15W/40

Description:

Maxol Powertrac 15W/40 is a multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade, solvent-refined base oils and additives.

- Powerful dispersion and detergency
- High activity against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent extreme pressure properties
- High and stable viscosity index

Application:

This multifunctional lubricant (known as a Super Tractor Oil Universal) has been developed to achieve one single lubricating oil that is able to lubricate:

- Gasoline engines
- Diesel engines (with or without turbo-charging)
- Transmissions (also "wet" brakes)
- Hydraulic systems

Performance Level:

API SF/CG-4/GL-4
ACEA E3
Massey Ferguson M1144/M1145
John Deere J27/20C
Ford M2C134-D
Massey Ferguson M1143
ZF TE-ML 06B/07B
Allison C4
MB 227.1

Typical Characteristics:

Density at 15 °C, kg/l	0.881
Viscosity -20 °C, mm ² /s	6400
Viscosity 40 °C, mm ² /s	93.50
Viscosity 100 °C, mm ² /s	13.00
Viscosity Index	137
Flash Point COC, °C	218
Pour Point, °C	-35
Total Base Number, mgKOH/g	11.3
Sulphate Ash, %	1.55

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

