Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Maxol Tractor Trans Plus

· Article number: NS-A.23.10

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC24 Lubricants, greases, release products

· Process category

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems

· Environmental release category

ERC4 Industrial use of processing aids in processes and products, not becoming part of articles

ERC7 Industrial use of substances in closed systems

ERC9a Wide dispersive indoor use of substances in closed systems

ERC9b Wide dispersive outdoor use of substances in closed systems

· Application of the substance / the mixture Transmission oil

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Smeermiddelen-Industrie

"De Oliebron" B.V.

Merwedeweg 17

3336 LG ZWIJNDRECHT (NL)

0031 (0)78 6101122

- · Further information obtainable from: Product safety department vib@socaz.com.
- 1.4 Emergency telephone number: +31 (0)78 6101122 (9 AM to 4 PM, Monday to Friday)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

(Contd. of page 1)

· Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains calcium sulphonate, triphenyl phosphite. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 64742-65-0 EINECS: 265-169-7 Reg.nr.: 01-2119471299-27	Distillates (petroleum), solvent-dewaxed heavy paraffinic Asp. Tox. 1, H304	50-100%
	Interchangeable low viscosity base oil (<20,5 cSt @40 °C) *	1-2.5%
Polymer	Benzene, polypropene derivatives, sulfonated, calcium salts Xi R36	1-2.5%
CAS: 4259-15-8 EINECS: 224-235-5 Reg.nr.: 01-2119493635-27	zinc-dialkyldithiophosphate Xi R41; N R51/53 Eye Dam. 1, H318; Aquatic Chronic 2, H411	1-2.5%
Polymer	calcium sulphonate Xi R43 ♦ Skin Sens. 1, H317	0.1-1.0%
CAS: 101-02-0 EINECS: 202-908-4	triphenyl phosphite Xn R22; Xi R36/38; Xi R43; N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-1.0%

· Additional information:

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact: Rinse opened eve for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

^{*} Contains one or more of the following CAS-numbers: 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-65-0, 64742-71-8, 68037-01-4, 72623-83-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 8042-47-5, 848301-69-9. For the wording of the listed risk phrases refer to section 16.

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, dry chemical, or foam. Water can be used to cool and protect exposed material.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Avoid the formation of oil haze.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

· Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves

Material of gloves

Nitrile rubber, NBR

PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Brown

Odour: Characteristic

· Change in condition

Boiling point/Boiling range: Undetermined.

· Drip point:

Pour point -42 °C (ASTM D97)

· Flash point: 195 °C

· Flammability (solid, gaseous): Not applicable.

· **Self-igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

• **Density at 20 °C:** 0.878 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Kinematic at 40 °C: 60 mm²/s

(Contd. on page 5)

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

(Contd. of page 4)

· Solvent content:

Organic solvents: 0.0 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

To avoid thermal decomposition do not overheat.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

101-02-0 triphenyl phosphite

Oral LD50 1600 mg/kg (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · Sensitisation For respiratory and skin sensitisation: Not expected to be a sensitiser.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Remark:

This material is expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

(Contd. of page 5)

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping nameADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
14.5 Environmental hazards:Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
 14.7 Transport in bulk according to Ann of MARPOL73/78 and the IBC Code 	ex II Not applicable.	
· UN "Model Regulation":	-	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 7)

Printing date 19.01.2015 Version number 1 Revision: 14.01.2015

Trade name: Maxol Tractor Trans Plus

(Contd. of page 6) H318 Causes serious eye damage. Causes serious eye irritation. H319 H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. R22 Harmful if swallowed. Irritating to eyes. R36 R36/38 Irritating to eyes and skin. R41 Risk of serious damage to eyes. **R43** May cause sensitisation by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Department issuing MSDS: Product safety department. · Contact: Product safety department · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

• Sources 67/548/EEC 99/45/EEC EC/453-2010

GE