

## Maxol Indusol 320

### Description:

High-grade industrial gear oil, based on mineral oil, under addition of lead-free Additives to obtain the following properties:

- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good rust
- and corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

### Application:

To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

### Performance Level:

AGMA 9005-F16 (AS)
AIST (US Steel) 224
David Brown S1.53.101 E
DIN 51517-3 CLP
ISO 12925-1 Type CKD

### Typical Characteristics:

Density at 15 °C, kg/l	0,904
Viscosity 40 °C, mm <sup>2</sup> /s	320,00
Viscosity 100 °C, mm <sup>2</sup> /s	24,00
Viscosity Index	95
Flash Point COC, °C	248
Pour Point, °C	-15

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

