

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** Maxol Gear Oil LS 90

· **Article number:**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against** ·

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites ·

Product category PC24 Lubricants, greases, release products

· **Process category**

PROC1 Use in closed process, no likelihood of exposure

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC8a Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at dedicated facilities

PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

· **Environmental release category**

ERC9a Wide dispersive indoor use of substances in closed systems

ERC9b Wide dispersive outdoor use of substances in closed systems

ERC4 Industrial use of processing aids in processes and products, not becoming part of articles

ERC7 Industrial use of substances in closed systems

· **Application of the substance / the mixture** Gear lubricant

· **1.3 Details of the supplier of the safety data sheet** ·

Manufacturer/Supplier:

Maxol Lubricants

Unit D, Airport Business Campus,

Santry,

Dublin 9

+353 (0) 1 806 0300

· **Further information obtainable from:** Product safety department - +353 (0) 1 806 0300.

· **1.4 Emergency telephone number:** +353 (0) 1 806 0300 (9 AM to 4 PM, Monday to Friday)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

The product is not classified according to the CLP regulation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC** Not applicable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008** Void ·

Hazard pictograms Void

· **Signal word** Void

· **Hazard statements** Void

· **Additional information:**

EUH208 Contains Reaction products of bis (4 -methylpentan - 2 -yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched). May produce an allergic reaction.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 1)

EUH210 Safety data sheet available on request. -

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 931-384-6 Reg.nr.: 01-2119493620-38	Reaction products of bis (4 - m e t h y l p e n t a n - 2 - y l) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched) ☒ Xn R22; ☒ Xi R41; ☒ Xi R43; ☒ N R51/53 ☒ Eye Dam. 1, H318; ☒ Aquatic Chronic 2, H411; ☒ Acute Tox. 4, H302; Skin Sens. 1, H317	1-2.5%
	Interchangeable low viscosity base oil (<20,5 cSt @40 °C) * ☒ Asp. Tox. 1, H304	1-2.5%
CAS: 112-90-3 EINECS: 204-015-5	(Z)-octadec-9-enylamine ☒ C R34; ☒ Xn R22-48/22-65; ☒ Xi R37-41; ☒ N R50/53 ☒ STOT RE 2, H373; Asp. Tox. 1, H304; ☒ Skin Corr. 1B, H314; Eye Dam. 1, H318; ☒ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ☒ Acute Tox. 4, H302; STOT SE 3, H335	0.1-1.0%

Additional information:

* Contains one or more of the following CAS-numbers: 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-65-0, 64742-71-8, 68037-01-4, 72623-83-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 8042-47-5, 848301-69-9.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents:**

CO₂, dry chemical, or foam. Water can be used to cool and protect exposed material. -

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Remove from the water surface (e.g. skim or suck off).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Avoid the formation of oil haze.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities** ·
Storage:
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle. ·
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7. ·
- 8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work. ·
- **Respiratory protection:** Not required.
- **Protection of hands:**



Wear gloves for the protection against chemicals according to EN 374.

- Oil resistant gloves
- **Material of gloves**
Nitrile rubber, NBR
PVC gloves

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 3)

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling ·

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties ·**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Brown
Odour:	Characteristic

- **Change in condition**

Boiling point/Boiling range:	Undetermined.
Drip point:	
Pour point	-30 °C (ASTM D97)

Flash point:	> 110 °C
Flammability (solid, gaseous):	Not applicable.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %

Density at 20 °C:	0.898 g/cm ³
--------------------------	-------------------------

Solubility in / Miscibility with water:	Not miscible or difficult to mix.
--	-----------------------------------

Partition coefficient (n-octanol/water):	Not determined.
---	-----------------

Viscosity:	
40 °C	150 mm ² /s (ASTM D445)

Solvent content:	
Organic solvents:	0.0 %
9.2 Other information	No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 4)

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Sensitisation**
For skin sensitisation: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation. May cause an allergic skin reaction in sensitive individuals.
For respiratory sensitisation: Not expected to be a sensitiser.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:**
- | | |
|------------|---------------------|
| EC50 (21d) | >100 mg/L (daphnia) |
|------------|---------------------|
- **12.2 Persistence and degradability** No further relevant information available. .
 - Other information:** The product is difficultly biodegradable.
 - **12.3 Bioaccumulative potential** No further relevant information available.
 - **12.4 Mobility in soil** No further relevant information available.
 - **Ecotoxicological effects:**
 - **Remark:** Harmful to fish
 - **Additional ecological information:**
 - **General notes:**
Harmful to aquatic organisms
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 - **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
 - **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 5)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
-----------	---

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, ADN, IMDG, IATA** Void

- **14.2 UN proper shipping name**

- **ADR, ADN, IMDG, IATA** Void

- **14.3 Transport hazard class(es)**

- **ADR, ADN, IMDG, IATA**

- **Class** Void

- **14.4 Packing group**

- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:**

- **Marine pollutant:** No

- **14.6 Special precautions for user**

Not applicable.

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **UN "Model Regulation":**

-

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **National regulations:**

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2015

Version number 2

Revision: 06.01.2015

Trade name: Maxol Gear Oil LS 90

(Contd. of page 6)

- H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
-
- R22 Harmful if swallowed.
 R34 Causes burns.
 R37 Irritating to respiratory system.
 R41 Risk of serious damage to eyes.
 R43 May cause sensitisation by skin contact.
 R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
 R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65 Harmful: may cause lung damage if swallowed.

· **Department issuing MSDS:** Product safety department. ·

Contact: Product safety department

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin

Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **Sources**

67/548/EEC

99/45/EEC

EC/453-2010