Maxol Lubricants

# Technical Data

## Maxol Indusol EP 100

### Description:

High-grade industrial gear oil, based on mineral oil, under addition of lead-free Additives to obtain the following properties:
- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good rust
- and corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

### Performance Level:

| |
|---|
| AGMA 9005-F16 (AS) |
| AIST (US Steel) 224 |
| David Brown S1.53.101 E |
| DIN 51517-3 CLP |
| ISO 12925-1 Type CKD |

### Application:

To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

### Typical Characteristics:

| | |
|---|---|
| Density at 15 °C, kg/l | 0,882 |
| Viscosity 40 °C, mm²/s | 100,00 |
| Viscosity 100 °C, mm²/s | 11,00 |
| Viscosity Index | 96 |
| Flash Point COC, °C | 235 |
| Pour Point, °C | -24 |

**Important:**
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST