

## Maxol Long Life Coolant

### Description:

A ready-to-use premium Long Life coolant, based on patented LOBRID PSi-OAT additive technology. This provides the following properties:

- excellent long-term corrosion protection and long-term stability
- very high acid neutralizing capacity, making very long drain intervals possible
- neutralizing the negative effects of flux residue which arises, among other things, in the production process of aluminium radiators
- free from amines, nitrites, borates and 2-ethylhexanoic acid
- fluorescent pink.

### Performance Level:

ASTM D3306
JIS K 2234
CNH JIC-501
Cummins 85T8-2
Deutz DQC CA-14
DTFR 29D120 / 29D100
Iveco 18-1830
MAN 324 Si-OAT
MB 326.5 / 326.0
MTU 5048
Toyota LLC 1WW/2WW
VW TL 774-L/J/G/F/D

### Application:

Can be used all year round in cooling systems of petrol and diesel engines. This modern customer-ready coolant has been developed, among other things, for the current generation of VAG models where VW prescribes a G12 EVO quality. This coolant is fully backward compatible and mixable with older VAG coolants with specifications G12 Plus, G12++ and G13. This coolant must be used undiluted.

### Typical Characteristics:

Density at 15°C, kg/l	1,072
pH – Value	8,0
Crystallization point	-37

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

