



Technical Data

Maxol TOR MT/LD Gear Oil 75w/80

Description

This gear oil is a synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent thermal stability
- a very high activity against wear, corrosion and foam
- a low pour point
- very high quality EP-properties
- good clutch-switch performance at low temperatures
- long durability
- fuel economy

Application

This gear oil is special developed for gearboxes under very heavy duty conditions together with high temperatures. This oil can also be used for extended drain intervals.

Specifications

API GL-4

MAN 341 Typ Z4

ZF TE-ML 01L / 02L / 16K

Meets the requirements of:

DAF

Eaton Europe (extended drain)

Iveco

Renault

Volvo 97307

ZF TE-ML 08 / 13 / 24A

Important:

Always observe the manufacturers specifications when selecting products.

Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie



Maxol TOR MT/LD Gear Oil 75w/80

Typicals

Density at 15 °C, kg/l	0,858
Viscosity 40 °C, mm ² /s	59,50
Viscosity 100 °C, mm ² /s	10,00
Viscosity Index	155
Flash Point COC, °C	218
Pour Point, °C	-39

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

