

Maxol Enersynth 0W/20

Description:

A fuel economy motor oil, developed according to the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Specifications:

ACEA A1/B1
ILSAC GF-7A
Meets the requirements of:
GM dexos 1 Gen 3
Chrysler MS 6395
Fiat 9.55535-CR1
Ford WSS-M2C947-A/B1 / WSS-M2C962-A1
GM 6094M

Application:

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. By its unique composition, this oil is also excellent for Hybrid and other Eco versions as brought by various OEM's in the market. Due to its special composition, this product may well be applied to very low temperatures, such as under arctic conditions may occur.

Typical Characteristics:

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	4820
Viscosity 40 °C, mm ² /s	44,80
Viscosity 100 °C, mm ² /s	8,40
Viscosity Index	166
Flash Point COC, °C	256
Pour Point, °C	-54
Total Base Number, mgKOH/g	10,4
Sulphate Ash, %	1,32

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

