

## Maxol Multivis 68

### Description:

A high grade EP multigrade hydraulic oil based on carefully selected solvent refined base oils under addition of additives to obtain the following properties:

- a high and stable viscosity index
- excellent wear
- preventing properties
- a very good activity against corrosion
- an excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- a low pour point

### Application:

This hydraulic fluid is of tailor-made quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that have to work under high pressures over a wide temperature range. This fluid is **not** compatible in systems, containing parts or equipment with a silver lining.

### Performance Level:

AFNOR NF E 48-603 HV
ASTM D 6158 HV
Cincinnati Machine P-69
Denison HF-0/HF-1/HF-2
DIN 51524-3 HVLP
Eaton Brochure 694 for 35VQ25A
GM LS-2
ISO 11158 HV

### Typical Characteristics:

Density at 15 °C, kg/l	0,875
Viscosity 40 °C, mm <sup>2</sup> /s	68,00
Viscosity 100 °C, mm <sup>2</sup> /s	11,20
Viscosity Index	157
Flash Point COC, °C	210
Pour Point, °C	-36
Total Base Number, mgKOH/g	0,40
Sulphate Ash, %	0,06

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

