

Maxol Supersynth FE 0W/20

Description:

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high Viscosity index and a well-balanced choice of advanced Additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Performance Level:

| |
|------------------------------------|
| ACEA C5, C6 |
| API SP Resource Conserving |
| ILSAC GF-6A |
| BMW Longlife-17 FE+ |
| Jaguar Land Rover STJLR.03.5006 |
| MB-Approval 229.71 / 229.72 |
| Ford WSS-M2C947-B1 / WSS-M2C962-A1 |
| Opel OV 040 1547 - A20 |
| Chrysler MS-12145 |
| Fiat 9.55535-GSX |

Application:

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. This oil is fully backward compatible with BMW Longlife-14 FE+.

Typical Characteristics:

| | |
|------------------------------------|-------|
| Density at 15°C, kg/l | 0,847 |
| Viscosity -35°C, mPa.s | 5260 |
| Viscosity 40°, mm ² /s | 41,60 |
| Viscosity 100°C mm ² /s | 8,30 |
| Viscosity Index | 179 |
| Flash Point COC, °C | 222 |
| Pour Point, °C | -51 |
| Total Base Number, mgKOH/g | 7,8 |
| Sulphate Ash, % | 0,77 |

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

