

Maxol Biomax Rock Breaker Oil

Description:

Maxol Biomax Rock Breaker Oil is a high-grade, biodegradable hydraulic oil based on vegetable oils under addition of additives.

- Extreme high and stable viscosity index
- Excellent wear-preventing properties
- Very good activity against corrosion
- Excellent stability against oxidation
- Very good deaerating and foam suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

Application:

This biodegradable hydraulic oil is ideal for heavy-duty hydraulic systems that have to work under high pressures over a wide temperature range. This hydraulic oil is especially developed for situations where pollution of the environment can be expected. This fluid is **not** compatible in systems containing parts or equipment with a silver lining.

Performance Level:

ISO 15380 HETG
CEC L-33-T-82 > 90% (3 weeks)

Typical Characteristics:

Density at 15 °C, kg/l	0.919
Viscosity 40 °C, mm ² /s	36.00
Viscosity 100 °C, mm ² /s	8.11
Viscosity Index	211
Flash Point COC, °C	302
Pour Point, °C	-25
Total Base Number, mgKOH/g	0.40
Sulphate Ash, %	0.06

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

