

## Maxol ZF Hydramax 46

### Description:

Maxol ZF Hydramax 46 is a high-grade zinc-free EP hydraulic oil based on selected solvent refined base oils having a natural viscosity index, under addition of additives.

- Excellent protection against wear
- Very good activity against rust and corrosion
- Excellent stability against oxidation
- Very good demulsification properties
- Very good deaerating and foam-suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

### Application:

This type of hydraulic fluid may be used for heavy duty hydraulic equipment, as well as for light-duty gearboxes and bearings. This hydraulic oil may also be used for lubrication systems, general lubrication and vacuum pumps (with the exclusion of turbines). This oil can be used in systems with silver parts.

### Performance Level:

DIN 51524-2 HLP
Denison HF-0/HF-1/HF-2
Cincinnati Machine P-70
Eaton (Vickers) M-2950-S
AIST (US Steel) 126/127/136
SEB 181 222
AFNOR NF E 48-603 HM
ISO 11158 HM
ISO 6743/4 HM

### Typical Characteristics:

Density at 15 °C, kg/l	0,865
Viscosity 40 °C, mm <sup>2</sup> /s	46.00
Viscosity 100 °C, mm <sup>2</sup> /s	6.90
Viscosity Index	103
Flash Point COC, °C	215
Pour Point, °C	-30
Acid number, mgKOH/g	0.12
Sulphate Ash, %	<0.01

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

