

Maxol Gas Engine Oil LA 40

Description:

Maxol Gas Engine Oil LA 40 is suitable for the lubrication of four stroke gas engines, when gases are used with lower sulphur contents.

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance
- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

Application:

This gas engine oil is suitable to apply in four stroke gas engines for which lower acid neutralisation capacity is required. This oil can be applied when natural gas, biomass gas or sewing gas are used. Application of this motor oil contributes to a longer lifetime and decreased maintenance costs, because longer service fill times are possible. Due to its lower phosphate content a longer lifetime of the catalyst can be achieved.

Typical Characteristics:

Density at 15 °C, kg/l	0.888
Viscosity 40 °C, mm ² /s	143.00
Viscosity 100 °C, mm ² /s	14.70
Viscosity Index	102
Flash Point COC, °C	254
Pour Point, °C	-21
Total Base Number mgKOH/g	5.1
Acid Number mgKOH/g	1.84
Sulphate Ash, %	0.45

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

