

## Maxol Multivis 15

### Description:

Maxol Multivis 15 is a high-grade EP multigrade hydraulic oil based on carefully selected solvent-refined base oils under addition of additives.

- High and stable viscosity index
- Excellent wear-preventing properties
- Very good activity against corrosion
- Excellent stability against oxidation
- Very good demulsification properties
- Very good deaerating and foam suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

### Application:

This hydraulic fluid is of tailormade quality for heavy duty hydraulic systems of earthmoving equipment and of permanent installations that have to work under high pressures over a wide temperature range. This fluid is not compatible in systems, containing parts or equipment with a silver lining.

### Performance Level:

DIN 51524-3 HVLP
AFNOR NF E 48-603 HV
ISO 11158 HV
ASTM D 6158 HV

### Typical Characteristics:

Density at 15 °C, kg/l	0.888
Viscosity 40 °C, mm <sup>2</sup> /s	15.60
Viscosity 100 °C, mm <sup>2</sup> /s	3.83
Viscosity Index	143
Flash Point COC, °C	152
Pour Point, °C	-60
Acid number, mgKOH/g	0.40
Sulphate Ash, %	0.06

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

