

## Maxol ATF Dexron III

### Description:

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- Very high and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Positive activity against wear, corrosion and foam
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals
- Red coloured

### Application:

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

### Performance Level:

Allison C4/TES-389
Cat TO-2
Ford Mercon/M2C138-CJ/166-H
GM Dexron IID/IIIE/IIIF/IIIG/IIIH
MAN 339 Typ Z1/V1
MB 236.1/236.5/236.6/236.7/236.9
Cat TO-2
Voith 55.6335 (G607)
ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C
Volvo 97341

### Typical Characteristics:

Density at 15 °C, kg/l	0,865
Viscosity 40 °C, mm <sup>2</sup> /s	37,70
Viscosity 100 °C, mm <sup>2</sup> /s	7,60
Viscosity Index	175
Flash Point COC, °C	210
Pour Point, °C	-51

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300 Web: [www.maxol.ie](http://www.maxol.ie)

