Maxol Lubricants

Technical Data

Maxol Petrol Engine Oil 15W/40

Description:

A modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to obtain the following properties:
– a strong detergency and dispersion power
– a strong resistance against oxidation
– a strong protection against wear
– a strong protection against corrosion and foaming
– a high and stable viscosity index
– a low tendency to evaporation

Performance Level:

ACEA A3/B4
API SP/CF
MB 229.1
VW 501.01/505.00

Application:

This modern multifunctional motor oil is recommended for use in petrol-, diesel-, and LPG-engines, with or without turbo-charging, in passenger cars and delivery vans.

Typical Characteristics:

Density at 15°C, kg/l	*0,868*
Viscosity -20 °C, mm²/s	*3660*
Viscosity 40 °C, mm²/s	*97,50*
Viscosity 100 °C, mm²/s	*14,30*
Viscosity Index	*145*
Flash Point COC, °C	*232*
Pour Point, °C	*-36*
Total Base Number, mgKOH/g	*10,4*
Sulphate Ash, %	*1,32*

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol LUBRICANTS YOU CAN TRUST

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie