

Maxol Premium HD 40

Description:

Maxol Premium HD 40 is produced with high-quality, solvent-refined base oils and a number of additives.

- High detergency and dispersion power
- Strong resistance against oxidation
- Effective in preventing from wear, corrosion and foam

Application:

Suitable lubricating oil for gasoline engines under light service conditions, moreover for the diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines, for which a minimum API CD or a Mil-L-2104C/D level oil is required.

Performance Level:

API SF/CC
CCMC G2/D1
Mil-L-46152B/C
Ford M2C153-C (SF/CC)
Ford M2C9011-A
GM 6085M

Typical Characteristics:

Density at 15 °C, kg/l	0.892
Viscosity 40 °C, mm ² /s	152.00
Viscosity 100 °C, mm ² /s	15.00
Viscosity Index	97
Flash Point COC, °C	245
Pour Point, °C	-12
Total Base Number, mgKOH/g	3.6
Sulphate Ash, %	0.55

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

