Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

SECTION 1: Identification	of the substance/mixture and of	f the company/undertaking
1.1 Product identifier		
· Trade name: Maxol Gas Engin	e Oil LA 40	
· Article number:		
 1.2 Relevant identified uses o Sector of Use 	f the substance or mixture and use	es advised against ·
SU22 Professional uses: I craftsmen)	Public domain (administration, educ	
	ubstances as such or in preparations a ouseholds / general public / consumer	
· Process category		
	ous process with occasional controlled tance or preparation (charging/disc	
PROC8b Transfer of subst	tance or preparation (charging/disc	charging) from /to vessels/large
	ansfer fluids in dispersive, professiona ce or preparation into small container	
Environmental release catego		
	por use of substances in closed syst or use of substances in closed systems	
	ssing aids in processes and products aces in closed systems	
• 1.3 Details of the supplier of t Manufacturer/Supplier: Maxol Lubricants Unit D, Airport Business Campus	-	
Santry, Dublin 9 +353 (0) 1 806 0300		
• Further information obtainab 0300. • 1.4 Emergency telephon +353 (0) 1 806 0300 (9 AM to 4 P		- +353 (0) 1 806
National Poison Information Cen Tel. nr. +31 30 - 2748888 - O intoxications.	tre (NVIC): only for the purpose of informing medi	ical personnel in case of acute
SECTION 2: Hazards identif	ication	
• 2.1 Classification of the substa • Classification according to R The product is not classified according	Regulation (EC) No 1272/2008	
2.2 Label elements Labelling according to Regula Hazard pictograms Void	ation (EC) No 1272/2008 Void	
 Signal word Void Hazard statements Void 		
 Additional information: 		
EUH208 Contains C14-16-18 A EUH210 Safety data sheet availa • 2.3 Other hazards	Nkyl phenol. May produce an allergic able on request.	c reaction.
· Results of PBT and vPvB asse	essment	
• PBT: Not applicable.		(Contd. on page 2)
		GB

Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

Trade name: Maxol Gas Engine Oil LA 40

· **vPvB:** Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:		
CAS: 68411-46-1	Benzenamine, N -phenyl-, reaction products with 2, 4,4-	1-2.5%
	trimethylpentene	
Reg.nr.: 01-2119491299-23		
CAS: 68457-79-4	Phosphorodithioic acid, mixed O,O-bis (iso-Bu and pentyl) 0	1-1.0%
EINECS: 270-608-0	esters, zinc salts	8
Reg.nr.: 01-2119493628-22	Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315	

· Additional information:

The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346. For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.
 4.2 Most important symptoms and effects, both acute and delayed
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed If

swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, dry chemical, or foam. Water can be used to cool and protect exposed material. .

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. ·

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).

• 6.4 Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling.

(Contd. on page 3)

GB

Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

(Contd. of page 2)

Trade name: Maxol Gas Engine Oil LA 40

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Avoid the formation of oil haze.

• Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities ·

Storage:

• Requirements to be met by storerooms and receptacles: Store only in the original receptacle. • Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Wash hands before breaks and at the end of work. • Respiratory protection: Not required.

· Protection of hands:



Wear gloves for the protection against chemicals according to EN 374.

Oil resistant gloves • Material of gloves

Nitrile rubber, NBR

PVC gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed.

Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling

(Contd. on page 4)

GB

Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

Trade name: Maxol Gas Engine Oil LA 40

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties				
 9.1 Information on basic physical and chemical properties General Information Appearance: 				
Form:	Liquid			
Colour:	Brown			
· Odour:	Characteristic			
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. Undetermined.			
Drip point: Pour point	-21 °C (ASTM D97)			
 Flash point: Flammability (solid, gaseous): Self-igniting: Danger of explosion: Explosion limits: 	> 110 °C Not applicable. Product is not selfigniting. Product does not present an explosion hazard.			
Lower: Upper:	0.6 Vol % 7.0 Vol %			
· Density at 20 °C:	0.885 g/cm ³			
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/wate	er): Not determined.			
· Viscosity: 40 °C	128 mm²/s (ASTM D445)			
 Solvent content: Organic solvents: 9.2 Other information 	0.0 % No further relevant information available.			

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: To

avoid thermal decomposition do not overheat.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

4 1. 0

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 5)

(Contd. of page 3)

GB

Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

Trade name: Maxol Gas Engine Oil LA 40

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

• Sensitisation For respiratory and skin sensitisation: Not expected to be a sensitiser.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available. ·
- Other information: The product is difficultly biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark:

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR,ADN, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, ADN, IMDG, IATA	Void	

(Contd. of page 4)

GP

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.06.2015

Version number 2

Revision: 03.06.2015

Trade name: Maxol Gas Engine Oil LA 40

		(Contd. of page 5)
 14.3 Transport hazard class(es) 		
· ADR,ADN, ADN, IMDG, IATA · Class	Void	
• 14.4 Packing group	Volu	
· ADR,ADN, IMDG, IATA	Void	
 14.5 Environmental hazards: Marine pollutant: 	No	
 14.6 Special precautions for user 	Not applicable.	
 14.7 Transport in bulk according to Annex of MARPOL73/78 and the IBC Code 	k II Not applicable.	
· UN "Model Regulation":	-	

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

- H318 Causes serious eye damage.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing MSDS: Product safety department. ·
- **Contact:** Product safety department
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment Chronic Hazard, Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment Chronic Hazard, Category 3
- Sources EC/453-2010