

## Maxol Extendo 5W30

### Description:

A fuel economy, synthetic, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

### Performance Level:

ACEA C3
API SP
VW 504.00 / 507.00
MB-Approval 229.51 / 229.52
BMW Longlife-04
Porsche C30
MB 229.31
Opel OV 040 1547 - D30 / G30

### Application:

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition, it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

### Typical Characteristics:

Density at 15°C, kg/l	0,852
Viscosity 40 °C, mm <sup>2</sup> /s	69,80
Viscosity -30 °C, mPa.s	5980
Viscosity 100 °C, mm <sup>2</sup> /s	12,30
Viscosity Index	176
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	0,75

### Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

