

Maxol Uni Gear 80W/90 LD

Description:

This universal gear oil is based on high quality solvent refined base oils and special EP-additives to obtain the following properties:

- Excellent activity against high temperature load
- Excellent activity against wear, corrosion and foam
- Low pour point
- Very special EP-properties
- Widely usable

Application:

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable. This product also contains excellent "Limited Slip" properties.

Performance Level:

API GL-3/GL-4/GL-5/MT-1
MIL-L-2105D / MIL-PRF-2105E, SAE J2360
DAF / DTFR 12B100
MAN 341 Typ Z2 / 341 Typ GA1 / 342 Type M2
Scania STO 1:0/ 1:1 G
ZF TE-ML 02B / 04G / 05A / 07A / 12E / 12M / 12L
ZF TE-ML 16B / 16C / 17H / 19B / 21A / 24A
MB 235.0
Mack GO-J
Iveco

Typical Characteristics:

Density at 15 °C, kg/l	0,902
Viscosity 40 °C, mm ² /s	146,40
Viscosity 100 °C, mm ² /s	15,20
Viscosity Index	105
Flash Point COC, °C	200
Pour Point, °C	-30

Important:

Always observe the manufacturers specifications when selecting products.

Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

