

Maxol Multitorc Fluid

Description:

A nowadays universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefore applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Performance Level:

API GL-4
Allison C4
Case MS1206 / MS1207 / MS1209
Cat TO-2
Ford M2C134-D
John Deere J20C
Massey Ferguson M1135 / M1143
NH 410B
Volvo WB 101 (97303)
ZF TE-ML 03E / 05F / 06K

Application:

This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment..

Typical Characteristics:

Density at 15°C, kg/l	0,887
Viscosity 40 °C, mPa.s	62,60
Viscosity 100 °C, mm²/s	10,60
Viscosity Index	155
Flash Point COC, °C	225
Pour Point, °C	-42

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

