

Technical Data

Maxol Enersynth 0W/20

Description:

A fuel economy motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application:

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. By its unique composition, this oil is also excellent for Hybrid and other Eco versions as brought by various OEM's in the market. Due to its special composition, this product may well be applied to very low temperatures, such as under arctic conditions may occur

Performance Level:

ACEA A1/B1

API SH/CF

API SN/CF *) *) API SN quality only; notlicensable due to phosphorus-limit

Typical Characteristics:

Density at 15°C, kg/l	0,846
Viscosity -35 °C, mPa.s	4590
Viscosity 40 °C, mm²/s	44,90
Viscosity 100 °C, mm²/s	8,35
Viscosity Index	162
Flash Point COC, °C	236
Pour Point, °C	-57
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32
Sulphale Ash, 70	1,52

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd. Unit D, Airport Business Campus, Santry, Dublin 9, Ireland. Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST