

Maxol ATF Dexron III

Description:

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals - red coloured

Performance Level:

Allison C4 / TES-389
Cat TO-2
DTRF 13C100 / 13C140 / 13C170 / 38B100
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID / IIE / IIIF / IIIG / IIIH / TASA
MAN 339 Typ Z1 / V1 / Z2
MB 236.1 / 236.3 / 236.5 / 236.6 / 236.7 / 236.9 / 236.10 / 236.93
Voith 55.6335 (G607)
Volvo 97340 / 97341 (AT101)
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Application:

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

Typical Characteristics:

Density at 15°C, kg/l	0,848
Viscosity 40 °C, mm ² /s	36,00
Viscosity 100 °C, mm ² /s	7,30
Viscosity Index	175
Flash Point COC, °C	226
Pour Point, °C	-48

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

