

Maxol Multitrac SS 10W/40

Description:

Maxol Multitrac SS 10W/40 is an up-to-date semi-synthetic multifunctional oil for agricultural and earthmoving equipment, formulated with top-grade solvent-refined and synthetic base oils and additives.

- Powerful dispersion and detergency
- High activity against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent extreme pressure properties
- High and stable viscosity index

Application:

This multifunctional lubricant, known as a super tractor oil universal, has been developed to achieve one single lubricating oil that is able to lubricate:

- Gasoline engines
- Diesel engines (with or without turbo-charging)
- Transmissions (also "wet" brakes)
- Hydraulic systems

Performance Level:

API SF/CG-4/GL-4
ACEA E3-96, Issue 5, Mil-L-2104D
Massey Ferguson CMS M1144/M1145
Ford M2C134-D
John Deere J20C
Massey Ferguson M1143
ZF TE-ML 06B/07B
Allison C4
MB 227.1
Cat TO-2

Typical Characteristics:

Density at 15 °C, kg/l	0.870
Viscosity -25°C, kg/l	4850
Viscosity 40 °C, mm ² /s	88.40
Viscosity 100 °C, mm ² /s	14.70
Viscosity Index	156
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	11.3
Sulphate Ash, %	1.55

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

