

Maxol UTTO WB HT

Description:

A very high quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure
- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Performance Level:

API GL-4
Allison C4
Case MS1207 / MS1209
Cat TO-2
John Deere J20A
Massey Ferguson M1141 / M1143 / M1145
Volvo WB 102 (97304)
ZF TE-ML 03E / 06K

Application:

This very high quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Typical Characteristics:

Density at 15 °C, kg/l	0,858
Viscosity 40 °C, mm ² /s	39,30
Viscosity 100 °C, mm ² /s	7,70
Viscosity Index	170
Flash Point COC, °C	224
Pour Point, °C	-42

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

