

Maxol Syntec 5W/40

Description:

A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- *a high and very stable viscosity index*
- *a high resistance against shearing*
- *a fast cold start*
- *a very strong resistance against oxidation*
- *a safe lubrication film at very high temperatures*
- *a very good detergency and dispersion*
- *a very strong protection against wear, corrosion and foaming*

Performance Level:

ACEA A3/B4
API SP / CF
MB 229.5 / 229.3 / 226.5
PSA B71 2296
Renault RN0700 / RN0710
VW 502.00 / 505.00
BMW Longlife-01
Fiat 9.55535-M2
GM LL-B-025
Porsche A40

Application:

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Typical Characteristics:

Density at 15°C, kg/l	0,853
Viscosity -30 °C, mPa.s	5880
Viscosity 40 °C, mm²/s	89,10
Viscosity 100 °C, mm²/s	14,70
Viscosity Index	168
Flash Point COC, °C	228
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,4
Sulphate Ash, %	1,32

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

