

TechnicalData

Maxol Universal Tractor Transmission Oil WB HT

Description:

Maxol Universal Tractor Transmission Oil WB HT is a high-quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives.

- High and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- High thermal stability
- Good extreme pressure- and anti-wear properties
- Optimal friction properties and therefor applicable in systems with "wet" brakes
- Excellent corrosion and foam preventing properties

Application:

This very high quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4
Volvo WB 102
Ford M2C134-D
Massey Ferguson M1141M1143
ZF TE-ML 03E/05F/06K
Allison C3/C4, John Deere J20A/C
Cat TO-2
Case MS1207/MS1209

Typical Characteristics:

31	
Density at 15 °C, kg/l	0.860
Viscosity 40 °C, mm²/s	41.00
Viscosity 100 °C, mm ² /s	7.70
Viscosity Index	164
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number,	10.2
mgKOH/g	

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

