Maxol Lubricants

Technical Data

Maxol Uni Gear LD 75W90

Description:

This gear oil is a universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

Performance Level:

API GL-4/GL-5/MT-1
MIL-L-2105D / MIL-PRF-2105E, SAE J2360
MAN 341 Typ Z2 / 342 Typ S1
MAN 3343 Typ S
Scania STO 1:0
Volvo 97310
ZF TE-ML 05C/07A/12B/12L/12N
ZF TE-ML 16B/16F/17B/19C/21C
P >1900 mg/kg (Liebherr)

Application:

Ma This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is a universal product widely usable.

Typical Characteristics:

Density at 15°C, kg/l	0,872
Viscosity 100 °C, mm²/s	98,00
Viscosity 40°C, mm²/s	16,70
Viscosity Index	185
Flash Point COC, °C	214
Pour Point, °C	-57
Total Base Number, mgKOH/g	2,1

Important:
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST