

TechnicalData

Maxol Lawmower Oil 10W/30

Description:

An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- Powerful dispersion and detergency
- High activity against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent extreme pressure properties
- High and stable viscosity index

Application:

This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate:

- Gasoline engines
- Diesel engines (with or without turbo-charging)
- Transmissions (also "wet" brakes)
- Hydraulic systems

(*) a so-called Super Tractor Oil Universal = STOU

Performance Level:

API SF/CG-4/GL-4	
ACEA E3	

Typical Characteristics:

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	6200
Viscosity 40 °C, mm²/s	66,30
Viscosity 100 °C, mm²/s	10,40
Viscosity Index	144
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,45
<u> </u>	

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

