Maxol Lubricants

# Technical Data

## Maxol Super Outboard

### Description:

*A* two stroke engine oil formulated with carefully selected high quality base oils and special ashless two stroke additives to achieve the following properties:
- an excellent lubricity
- a minimal carbon build-up
- a reduced spark plug fouling
- a limited formation of smoke
- a powerful detergency and activity against wear and corrosion
- excellent high temperature properties.

### Performance Level:

NMMA TC-W3

### Application:

*This* two stroke motor oil is advised for all outboard engines and is used in a ratio of 1 part of oil to 50 parts of gasoline. Other mixing ratios are also possible, it is recommended to adhere to the mixing ratio prescribed by the manufacturer.

### Typical Characteristics:

| | |
|---|---|
| ***Density at 15°C, kg/l*** | ***0,882*** |
| ***Viscosity 40 °C, mm²/s*** | ***88,30*** |
| ***Viscosity 100 °C, mm²/s*** | ***6,70*** |
| ***Viscosity Index*** | ***127*** |
| ***Flash Point COC, °C*** | ***114*** |
| ***Pour Point, °C*** | ***-39*** |

**Important:**
Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**
Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

Maxol LUBRICANTS YOU CAN TRUST