

Maxol Bio Hydrasynth Eco 32

Description:

This is a high-quality hydraulic oil based on biodegradable synthetic esters under addition of additives to obtain the following properties:

- a high and stable viscosity index
- excellent wear
- preventing properties
- a very good activity against corrosion
- an excellent stability against oxidation (even at high temperatures)
- very good deaerating and foam suppressing properties
- a good compatibility with seals and gaskets made from synthetic material
- a very low pour point
- good water separation
- reduced harm for water and soil during use
- contains a large fraction of biobased material

Performance Level:

EU Ecolabel
ISO 15380 HEES
Swedish Standard SS 15 54 34
Biodegradability according OECD 301 B > 70%
Elastomer compatibility:
Tested Nitrile Butadiene NBR1-pass
Tested Fluor Carbon FMK2-pass

Application:

This biodegradable hydraulic oil is of high quality and suitable for heavy duty hydraulic systems of earthmoving equipment and permanent installations, that have to work under high pressures over a wide temperature range. This hydraulic oil is especially developed for situations where pollution of the environment is expected and and where very high operating temperatures can be realised.

Typical Characteristics:

Density at 15 °C, kg/l	0,930
Viscosity 40 °C, mm ² /s	33,20
Viscosity 100 °C, mm ² /s	6,95
Viscosity Index	177
Flash Point COC, °C	280
Pour Point, °C	-51
Acid Number mgKOH/g	0,60

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

