

Maxol Super Diesel 10W

Description:

Maxol Super Diesel 10W is produced with high quality solvent refined base oils and a number of additives.

- High detergency and dispersion power
- Strong resistance against oxidation
- Effective in preventing from wear, corrosion and foam

Application:

Suitable lubricating oil for gasoline engines under light service conditions, as well as for the diesel engines of passenger cars and light delivery vans. Not applicable for turbo-charged diesel engines, for which a minimum API CD or a Mil-L-2104C/D level oil is required.

Performance Level:

| |
|-----------------------|
| API SF/CC |
| CCMC G2/D1 |
| Mil-L-46152B/C |
| Ford M2C153-C (SF/CC) |
| Ford M2C9011-A |
| GM 6085M |

Typical Characteristics:

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0.864 |
| Viscosity -25 °C, mPa.s | 6000 |
| Viscosity 40 °C, mm ² /s | 38.20 |
| Viscosity 100 °C, mm ² /s | 5.60 |
| Viscosity Index | 98 |
| Flash Point COC, °C | 205 |
| Pour Point, °C | -30 |
| Total Base Number, mgKOH/g | 3.6 |
| Sulphate Ash, % | 0.55 |

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

