

Technical Data

Maxol Extendo 5w/30

Description

A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

Application

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Specifications

ACEA C3 Approved under VW 504.00/507.00 MB-Approval 229.31/229.51 BMW Longlife-04 Meets the requirements of : MB 229.52 Opel OV0401547

API SP Porsche C30

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.



Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland. Tel: +353 (0) 1 806 0300 Web: www.maxol.ie



TechnicalData

Maxol Extendo 5w/30

Typicals

Density at 15 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	5980
Viscosity 40 °C, mm²/s	69,80
Viscosity 100 °C, mm²/s	12,30
Viscosity Index	176
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	0,75

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.



Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland. Tel: +353 (0) 1 806 0300 Web: www.maxol.ie