

Maxol Uni Gear LD 75W/90

Description:

This gear oil is an universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- Excellent activity against high temperature load
- Very strong activity against wear, corrosion and foam
- Low pour point
- Very special extreme pressure properties
- Widely usable

Application:

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable. This product also contains excellent "Limited Slip" properties.

Performance Level:

API GL-4/GL-5/MT-1
Mil-L-2105D, Mil-PRF-2105E, SAE J2360
ZF TE-ML 05C/07A/12B/12L/12N
ZF TE-ML 16B/16F/17B/19C/21C
MAN 3343 Typ S
MAN 341 Typ Z2, 342 Typ S1,
Scania STO 1:0
Volvo 97310

Typical Characteristics:

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm ² /s	113,70
Viscosity 100 °C, mm ² /s	16,50
Viscosity Index	157
Flash Point COC, °C	202
Pour Point, °C	-42
Total Base Number, mgKOH/g	2,1

Important:

Always observe the manufacturers specifications when selecting products.

Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

