

## Maxol Indusol EP 220

### Description:

Maxol Indusol EP 220 is a high-grade industrial gear oil, based on mineral oil, under addition of lead-free EP-additives.

- Very good resistance towards high pressures and shock loads
- Good resistance against high temperatures
- Good corrosion preventing properties
- Excellent prevention from wear
- Very good activity against foaming
- Low pour point

### Application:

To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

### Performance Level:

DIN 51517-3 CLP
AGMA 9005-E02
US Steel 224
David Brown S1.53.101(E)

### Typical Characteristics:

Density at 15 °C, kg/l	0.894
Viscosity 40 °C, mm <sup>2</sup> /s	220.00
Viscosity 100 °C, mm <sup>2</sup> /s	18.10
Viscosity Index	95
Flash Point COC, °C	245
Pour Point, °C	-20

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

### Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.  
Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

