

Maxol Tor Truck Fleet LSP 10W/40

Description:

This Heavy Duty engine oil is formulated with unique low SAPS high performance additives in combination with special selected base oils. This multigrade engine oil fulfills the latest requirements of OEM's for use in high speed four stroke diesel engines of the latest models and has the following properties:

- meets or exceeds the requirement of the nowadays low emission standards
- excellent cold start properties
- a very good shear stability
- an improved oxidation resistance
- a very strong dispersion, therefore the deposits and sludge are restricted to a minimum
- excellent properties against wear, corrosion and foam

Application:

This Heavy Duty engine oil is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels benefits highly to the lifetime of emission control systems. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 and Euro 6 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines, when indicated by the manufacturer.

Performance Level:

ACEA E6, E7, E9
API CK-4/SN
Deutz DQC IV-10LA
Mack EOS-4.5
MAN M 3477
MB 228.51
Renault VI RLD-4
Volvo VDS-4.5
Cat ECF-3
Cummins CES 20086
Detroit Diesel 93K222/93K218
JASO DH-2
MTU Type 2.1

Typical Characteristics:

Density at 15 °C, kg/l	0,872
Viscosity -25 °C, mPa.s	6410
Viscosity 40 °C, mm ² /s	98,20
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	153
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,98

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.
Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

