

	SAFETY DATA SHEET	Page : 1 / 11
	Maxol Antifreeze	Revision nr : 2.0
		Issue date : 23/11/2023
		Supersedes : 02/03/2022

SECTION: 1. Product and company identification

1.1. Product identifier

Trade name/designation : C2230
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Main use category : Industrial use, Professional use, Consumer use
Specific end use(s) : Antifreeze

1.3. Details of the supplier of the safety data sheet

Company : Maxol Lubricants Limited
Unit D, Airport Business Campus
Santry
Dublin 9, Ireland
E-mail: lubricants@maxol.ie

1.4. Emergency telephone number

Emergency telephone : In case of poisoning, call your poison control center at 1-800-222-1222

SECTION: 2. Hazards identification

2.1. Classification of the substance or mixture

OSHA Regulatory Status : This material is classified as hazardous under OSHA regulations.
GHS-US classification : Acute toxicity (oral), Category 4
GHS-US classification : Reproductive toxicity, Hazard Category 2
GHS-US classification : Specific target organ toxicity – Repeated exposure, Category 2

2.2. Label elements

Hazard pictograms (GHS US) :



GHS07 GHS08

Signal word (GHS US) :

: Warning

Hazard statements (GHS US) :

: Harmful if swallowed.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS US) :

: If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe vapours, spray.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves, protective clothing, eye protection, face protection.
If swallowed: Call a POISON CENTER, a doctor if you feel unwell.
If exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Rinse mouth.
Store locked up.
Dispose of contents/container to an approved waste disposal plant.

	SAFETY DATA SHEET	Page : 2 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

2.3. Other hazards

Other hazards which do not result in classification : Not applicable

SECTION: 3. Composition/information on ingredients

Substance name	CAS-No.	%
ethanediol; ethylene glycol	107-21-1	> 90 – < 95
dipotassium tetraborate	1332-77-0	1 – 1,5

SECTION: 4. First aid measures

4.1. Description of first aid measures

Inhalation	: Remove casualty to fresh air and keep warm and at rest In case of doubt or persistent symptoms, consult always a physician
Skin contact	: Remove contaminated clothing and shoes Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician
Ingestion	: Rinse mouth thoroughly with water Get medical advice/attention.
Additional advice	: First aider: Pay attention to self-protection! Concerning personal protective equipment to use, see section 8 Never give anything by mouth to an unconscious person In case of doubt or persistent symptoms, consult always a physician Show this safety data sheet to the doctor in attendance.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: The following symptoms may occur: Irritating to respiratory system, Cough, Dizziness, Headache.
Skin contact	: May be absorbed through the skin. The following symptoms may occur: Dry skin, Irritation Chronic exposure may cause dermatitis.
Eyes contact	: The following symptoms may occur: erythema (redness), Pain, Eye irritation.
Ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhoea The following symptoms may occur: Abdominal pain, Drowsiness, Dizziness, Headache, Unconsciousness, Impairment of the nervous system, Liver and kidney injuries may occur.
Other adverse effects	: May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION: 5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, alcohol resistant foam, Dry extinguishing powder, Carbon dioxide

	SAFETY DATA SHEET	Page : 3 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

For safety reasons unsuitable extinguishing agents : Strong water jet

5.2. Special hazards arising from the substance or mixture

Fire hazard : Non flammable
 Specific hazards : Heating will cause a rise in pressure with a risk of bursting
 Hazardous decomposition products in case of fire :
 Carbon oxides,
 Burning produces noxious and toxic fumes.

5.3. Advice for firefighters

Advice for firefighters : Special protective equipment for firefighters.
 In case of fire: Wear self-contained breathing apparatus.
 Use water spray or fog for cooling exposed containers
 Do not allow run-off from fire-fighting to enter drains or water courses.
 Dispose of waste in accordance with environmental legislation
 Evacuate personnel to a safe area

SECTION: 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Evacuate personnel to a safe area
 Stay upwind/keep distance from source
 Provide adequate ventilation
 Do not breathe vapour/aerosol
 Avoid contact with skin, eyes and clothing
 Use personal protective equipment as required.
 Concerning personal protective equipment to use, see section 8
 Do not allow to enter into surface water or drains
 Notify authorities if product enters sewers or public waters

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place
 Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains
 Notify authorities if product enters sewers or public waters

6.2. Methods and material for containment and cleaning up

Spill or leak statements by chemical : Stop leak if safe to do so.
 Dam up the liquid spill
 Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal
 Recover large spills by pumping (use an explosion proof or hand pump)
 Place in a suitable container for disposal in accordance with the waste regulations (see Section 13)
 This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION: 7. Handling and storage

7.1. Precautions for safe handling

Handling : Provide adequate ventilation
 Do not breathe vapour/aerosol

	SAFETY DATA SHEET	Page : 4 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

Avoid contact with skin, eyes and clothing
 Use personal protective equipment as required.
 Concerning personal protective equipment to use, see section 8
 Take any precaution to avoid mixing with incompatible materials.
 See also section 10
 Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time).
 Do not allow contact with soil, surface or ground water.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advices on general occupational hygiene : Keep good industrial hygiene
 Wash hands before breaks and immediately after using the product.
 When using do not eat, drink or smoke.
 Keep away from food, drink and animal feedingstuffs
 Keep work clothes separately.
 Remove contaminated clothing and shoes
 Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep in a dry, cool and well-ventilated place.
 Do not store near or with any of the incompatible materials listed in section 10.
 Bund storage facilities to prevent soil and water pollution in the event of spillage.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Protect from moisture.

Packaging materials : Keep/Store only in original container.
 Suitable material: Stainless steel, Carbon steel, Glass
 Tactile warning

SECTION: 8. Exposure controls/personal protection

8.1. Exposure guidelines

ethanediol; ethylene glycol (107-21-1)		
ACGIH	ACGIH OEL TWA [ppm]	25 ppm (vapor fraction)
ACGIH	ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH	ACGIH OEL STEL [ppm]	50 ppm (vapor fraction)
Québec	Plafond (OEL C)	127 mg/m ³ (mist and vapour)
Québec	Plafond (OEL C) [ppm]	50 ppm (mist and vapour)

8.2. Engineering controls

Engineering measure(s) : Provide adequate ventilation
 Organisational measures to prevent/limit releases, dispersion and exposure
 See Section 7 for information on safe handling .

Environmental exposure controls : Do not allow contact with soil, surface or ground water.
 Comply with applicable Community environmental protection legislation.

8.3. Personal protective equipment (PPE)

Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

	SAFETY DATA SHEET	Page : 5 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment
 Full face mask
 Half-face mask
 Filter type: A
 The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Wear chemically resistant gloves (tested to EN374) Suitable material: Neoprene, Nitrile rubber Breakthrough time : > 8 hours Thickness of the glove material: > 0,3 mm Suitable material: Butyl rubber, natural rubber gloves, Polyethylene, Polyvinylchloride (PVC), VITON gloves, Polyvinylalcohol (PVA), Chlorinated polyethylene, Polyurethane Breakthrough time : refer to the recommendations of the supplier Thickness of the glove material: Not determined The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
- Eye protection : Use suitable eye protection : tightly fitting safety goggles During splash contact: face shield
- Body protection : Wear suitable coveralls to prevent exposure to the skin
- Thermal hazard protection : Not required for normal conditions of use
 Use dedicated equipment

SECTION: 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Appearance : Liquid
- Colour : Colourless
- Odour : odourless
- Odour threshold : No data available
- pH : 8,4 (50%)
- Melting / freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : 111 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable, liquid
- Upper / lower flammability or explosive limits : No data available
- Vapour pressure : No data available
- Vapour density : No data available
- Density : 1125 kg/m³ (20°C)
- Relative density : 1,13 (20°C)
- Water solubility : Soluble
- Solubility in different media : No data available
- Partition coefficient n-octanol/water : No data available
- Auto-ignition temperature : > 400 °C
- Decomposition temperature : No data available
- Viscosity : No data available
- Explosive properties : Not applicable, The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.

	SAFETY DATA SHEET	Page : 6 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

SECTION: 10. Stability and reactivity

10.1.Reactivity

Reactivity : Hygroscopic product
Reference to other sections 10.5

10.2.Chemical stability

Chemical stability : The product is stable under storage at normal ambient temperatures.

10.3.Possibility of hazardous reactions

Possibility of hazardous reactions : None under normal processing.

10.4.Conditions to avoid

Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Protect from moisture.
See Section 7 for information on safe handling

10.5.Incompatible materials

Incompatible materials : oxidising substances Strong bases Strong acids Aluminium Sulphuric acid
Perchloric acid Chlorosulfonic acid Sodium hydroxide See also section 7

10.6.Hazardous decomposition products

Hazardous decomposition products : Reference to other sections 5.2

SECTION: 11. Toxicological information

11.1.Information on toxicological effects

Acute toxicity : Harmful if swallowed

ethanediol; ethylene glycol (107-21-1)	
LD50/oral/rat	7712 mg/kg bodyweight
LD50/dermal/rat	10600 mg/kg
LD50/dermal/rabbit	> 3500 mg/kg
LC50/inhalation/4h/rat	> 2,5 mg/l (Exposure time: 6 h)
dipotassium tetraborate (1332-77-0)	
LD50/oral/rat	3690 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg (Source: ECHA_API)
LC50/inhalation/4h/rat	> 2,04 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 8,4 (50%)

Serious eye damage/irritation : Not classified
pH: 8,4 (50%)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

ethanediol; ethylene glycol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1000 mg/kg bodyweight

	SAFETY DATA SHEET	Page : 7 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

ethanediol; ethylene glycol (107-21-1)	
NOAEL (chronic, oral, animal/female, 2 years)	1500 mg/kg bodyweight

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

ethanediol; ethylene glycol (107-21-1)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight/day OECD Guideline 407
NOAEL (dermal, rat/rabbit, 90 days)	2220 mg/kg bodyweight/day OECD 410

Aspiration hazard : Not classified

Other adverse effects : May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

SECTION 12: Ecological information

12.1.Toxicity

Toxicity : Ecological injuries are not known or expected under normal use.

ethanediol; ethylene glycol (107-21-1)	
LC50 - Fish [1]	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC (chronic)	15380 mg/l (7d, Pimephales promelas)

dipotassium tetraborate (1332-77-0)	
LC50 - Fish [1]	79,7 mg/l
EC50 - Crustacea [1]	130 mg/l

12.2.Persistence and degradability

Persistence and degradability : No data available

12.3.Bioaccumulative potential

Bioaccumulative potential : No data available

Partition coefficient n-octanol/water : No data available

12.4.Mobility in soil

Mobility in soil : No data available

12.5.Other adverse effects

Other information : No data available

	SAFETY DATA SHEET	Page : 8 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Product waste: : Do not allow contact with soil, surface or ground water.
 Dispose of empty containers and wastes safely
 See Section 7 for information on safe handling
 Refer to manufacturer/supplier for information on recovery/recycling
 Recycling is preferred to disposal or incineration
 If recycling is not possible, eliminate in accordance with local valid waste disposal regulations
- Contaminated packaging : Handle contaminated packages in the same way as the substance itself.
 Dispose of contaminated materials in accordance with current regulations
 Beware of residues or vapours which remain in the drums

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

SECTION: 15. Regulatory information

15.1. US Federal regulations

ethanediol; ethylene glycol (107-21-1)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 5000 lb

SARA Section 313 - Emission Reporting 1 %

15.2. International regulations

15.2.1. CANADA

ethanediol; ethylene glycol (107-21-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

15.2.2. National regulations

ethanediol; ethylene glycol (107-21-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

	SAFETY DATA SHEET	Page : 9 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

15.3. US State regulations

ethanediol; ethylene glycol (107-21-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

dipotassium tetraborate (1332-77-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

ethanediol; ethylene glycol (107-21-1)


- U.S. - New Jersey - Right to Know Hazardous Substance List
- U.S. - Pennsylvania - RTK (Right to Know) List
- U.S. - Minnesota - Hazardous Substance List
- U.S. - Massachusetts - Right To Know List
- U.S. - New Jersey - Environmental Hazardous Substances List
- U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. - Illinois - Toxic Air Contaminants
- U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
- U.S. - Tennessee - Occupational Exposure Limits - Ceilings
- U.S. - Massachusetts - Toxics Use Reduction Act
- U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
- U.S. - Vermont - Permissible Exposure Limits - Ceilings
- U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
- U.S. - Washington - Permissible Exposure Limits - Ceilings
- U.S. - Massachusetts - Threshold Effects Exposure Limits (TELs)
- U.S. - Massachusetts - Allowable Ambient Limits (AALs)
- U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
- U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
- U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
- U.S. - New York - Occupational Exposure Limits - Ceilings
- U.S. - Michigan - Occupational Exposure Limits - Ceilings
- U.S. - Minnesota - Permissible Exposure Limits - Ceilings
- U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
- U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
- U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
- U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
- U.S. - Oregon - Permissible Exposure Limits - TWAs
- U.S. - Texas - Effects Screening Levels - Long Term
- U.S. - Texas - Effects Screening Levels - Short Term
- U.S. - Michigan - Polluting Materials List
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
- U.S. - Massachusetts - Drinking Water Guidelines
- U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
- U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
- U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
- U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
- U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
- U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
- U.S. - Maine - Air Pollutants - Hazardous Air Pollutants

	SAFETY DATA SHEET	Page : 10 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

ethanediol; ethylene glycol (107-21-1)

- U.S. - Minnesota - Groundwater Health Risk Limits
- U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
- U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
- U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
- U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
- U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
- U.S. - Minnesota - Chemicals of High Concern
- U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups

SECTION: 16. Other information

- Issue date : 23/11/2023
Supersedes : 02/03/2022
Abbreviations and acronyms : BTT = Breakthrough time (maximum wearing time)
DOT= Department of Transport
EC50 = Median Effective Concentration
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
STOT = Specific Target Organ Toxicity
TWA = time weighted average
VOC = Volatile organic compounds
- Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.
- NFPA-code**
NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.
- 
- Hazard Rating**
Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 1 Slight Hazard
Physical : 1 Slight Hazard

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any

	SAFETY DATA SHEET	Page : 11 / 11
		Revision nr : 2.0
	Maxol Antifreeze	Issue date : 23/11/2023
		Supersedes : 02/03/2022

way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.