

Maxol Supersynth 5W/30

Description:

A synthetic universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:

- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Performance Level:

ACEA C2, C3
API SN
BMW Longlife-04
GM dexos 2
MB 229.51 / 229.52
Opel OV 040 1547 - D30
VW 505.01

Typical Characteristics:

Density at 15°C, kg/l	0,855
Viscosity -30 °C, mPa.s	6000
Viscosity 40 °C, mm ² /s	73,00
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	163
Flash Point COC, °C	230
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77

Important:

Always observe the manufacturers specifications when selecting products. Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

