

## Maxol Petrol Engine Oil 15W/40

### Description:

A modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to obtain the following properties:

- a strong detergency and dispersion power
- a strong resistance against oxidation
- a strong protection against wear
- a strong protection against corrosion and foaming
- a high and stable viscosity index
- a low tendency to evaporation

### Performance Level:

ACEA A3/B4
API SN/CF
MB 229.1
VW 501.01/505.00

### Application:

This modern multifunctional motor oil is recommended for use in petrol-, diesel-, and LPG-engines, with or without turbo-charging, in passenger cars and delivery vans.

### Typical Characteristics:

Density at 15°C, kg/l	0,877
Viscosity -20 °C, mm <sup>2</sup> /s	4070
Viscosity 40 °C, mm <sup>2</sup> /s	105,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,70
Viscosity Index	145
Flash Point COC, °C	230
Pour Point, °C	-30
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32

### Important:

Always observe the manufacturers specifications when selecting products.  
Maxol Lubricants reserve the right to change this product specification without notice.

**Maxol Lubricants Ltd.**

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300      Web: [www.maxol.ie](http://www.maxol.ie)

