

Maxol Superfarm 15W/30

Description:

An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- Powerful dispersion and detergency
- High activity against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent extreme pressure properties
- High and stable viscosity index

Application:

This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate:

- Gasoline engines
- Diesel engines (with or without turbo-charging)
- Transmissions also "wet" brakes)
- Hydraulic systems

(*) a so-called Super Tractor Oil Universal = STOU

Performance Level:

API SF/CG-4/GL-4
ACEA E3
Ford M2C159-C
Massey Ferguson M1139/M1144/M1145
John Deere J20C
Ford M2C134-D
Massey Ferguson M1135/M1143
ZF TE-ML 06B/07B
Allison C4
MB 227.1

Typical Characteristics:

Density at 15 °C, kg/l	0,884
Viscosity -20 °C, mPa.s	6000
Viscosity 40 °C, mm ² /s	76,60
Viscosity 100 °C, mm ² /s	10,50
Viscosity Index	122
Flash Point COC, °C	220
Pour Point, °C	-35
Total Base Number, mgKOH/g	10,9
Sulphate Ash, %	1,45

Important:

Always observe the manufacturers specifications when selecting products.

Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

