

Maxol Performance 10W/40

Description:

This universal motor oil is produced with special base oils that have a natural high viscosity index, to which additives are added to obtain the following properties:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a safe lubrication film at high temperature
- a good detergency and dispersion
- a strong protection against wear, corrosion and foaming

Performance Level:

ACEA A3/B4, PSA B71 2300
API SL/CF
MB 229.3
VW 501.01/505.00, Renault RN0700/ RN0710

Application:

A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Typical Characteristics:

Density at 15°C, kg/l	0,866
Viscosity -25 °C, mPa.s	5690
Viscosity 40 °C, mm ² /s	100,00
Viscosity 100 °C, mm ² /s	15,00
Viscosity Index	157
Flash Point COC, °C	238
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,32

Important:

Always observe the manufacturers specifications when selecting products.
Maxol Lubricants reserve the right to change this product specification without notice.

Maxol Lubricants Ltd.

Unit D, Airport Business Campus, Santry, Dublin 9, Ireland.

Tel: +353 (0) 1 806 0300 Web: www.maxol.ie

